

MATERIAL SAFETY DATA SHEET

OG6 5% alcoholic stain

Page 1 of 2
Date of Issue: 18 Sept. 06

STATEMENT OF HAZARDOUS NATURE

Not classified as hazardous according to criteria of Worksafe Australia

COMPANY DETAILS

Company: ProSciTech
Address: PO Box 111, Thuringowa Central Qld. 4817 Australia
Street Address: 1/11 Carlton Street, Kirwan, Qld. 4817 Australia
Telephone Number: (07) 4773 9444
Fax Number: (07) 4773 2244

IDENTIFICATION SECTION

Product Name	OG6 5% alcoholic stain
Other Names	Pap smear stain concentrate without dangerous goods
Product Code	AOG6-500
U.N. Number	None allocated
Dangerous Goods Class and Subsidiary Risk	None allocated
Hazchem Code	None allocated
Poison Schedule	None allocated
Use	Used in Hospital and Pathology laboratories to make OG6 Stain for Cytology staining

Physical Description and Properties

Appearance	Orange liquid
Boiling Point/Melting Point	100°C / 0°C
Vapour Pressure	23hPa @ 20°C
Specific Gravity	1.0
Flash Point	
Flammability Limits	Not determined
Solubility in water	Soluble in all proportions

Other Properties

Ingredients

Chemical Name	CAS Number	Proportion
Orange G C.I.16230 (Below Cutoff)	1936-15-8	1.4%
ACETIC ACID ... % (Below Cutoff)	64-19-7	4%
PHOSPHOTUNGSTIC ACID (Below Cutoff)	12501-23-4	0.08%
WATER AND OTHER NON-HAZARDOUS SUBSTANCES	Mixture	94.52%

OG6 5% alcoholic stain**HEALTH HAZARD INFORMATION****Health Effects:***Acute*

Swallowed:	May cause irritation to mouth, throat and stomach with effects including mucous build up, irritation to the tongue and lips and pains in the stomach.
Eye:	May cause irritation to the eyes, with effects including: tearing, pain, stinging and blurred vision.
Skin:	May cause irritation to the skin, with effects including; Redness and itchiness.
Inhaled:	May cause irritation to the nose, throat and respiratory system with effects including: Dizziness, headache and possible confusion.

*Chronic:***First Aid:**

Swallowed:	If swallowed, DO NOT induce vomiting. If victim is conscious give water. If sickness persists transport to hospital or doctor.
Eye:	If material is splashed into eyes, immediately flush with plenty of water for 15 minutes, ensuring eye lids are held open. If irritation persists transport to hospital or doctor.
Skin:	If material is splashed onto the skin, remove any contaminated clothing and wash skin thoroughly with water and soap if available. If irritation persists transport to hospital or doctor.
Inhaled:	Move victim to fresh air. Apply resuscitation if victim is not breathing - If trained personnel available administer oxygen if breathing is difficult.
First Aid Facilities:	Eye wash fountain, safety shower and normal wash room facilities.
Advice to Doctor	Treat symptomatically.

PRECAUTIONS FOR USE

Exposure Standards:	ACETIC ACID ... % (Below Cutoff) (Worksafe Australia) [TWA]10 ppm 25 mg/m ³ [STEL]15 ppm 37 mg/m ³
	Notices: H
	(ACGIH) [TWA]10 ppm 25 mg/m ³ [STEL]15 ppm 37 mg/m ³
Engineering Controls:	Maintain adequate ventilation at all times. In most circumstances natural ventilation systems are adequate unless the material is heated, reacted or otherwise changed in some type of chemical reaction, then the use of a local exhaust ventilation system is recommended.
Personal Protection:	CLOTHING: PVC or natural rubber apron or splash suit. GLOVES: PVC or natural rubber. EYES: Chemical goggles or faceshield to protect eyes. RESPIRATORY PROTECTION: Avoid breathing of vapours/gases. Select and use respirators in accordance with AS/NZS 1715/1716. The use of a P1 dust mask (disposable) or with replaceable filters is recommended. Filter capacity and respirator type depends on exposure levels and type of contaminant. If entering spaces where the airborne concentration of a contaminant is unknown then the use of a Self-contained breathing apparatus (SCBA) with positive pressure air supply complying with AS/NZS 1715 / 1716, or any other acceptable International Standard is recommended.
Flammability:	This material is not a flammable or combustible liquid.

OG6 5% alcoholic stain**SAFE HANDLING INFORMATION**

Storage and Transport:	Store in a cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidizing agents. Keep containers closed, when not using the product. Store in original packages as approved by manufacturer.
Spills and Disposal:	Material may be slippery when spilt. Walk cautiously. Ventilate area. Wear protective equipment to prevent skin and eye contact, as outlined under personal protection in this MSDS. Bund area using sand or soil - to prevent run off into drains and waterways. Use absorbent (soil, sand, vermiculite or other inert material). Collect and seal in properly labelled containers for disposal. Remainder of material can be washed to drain with plenty of water.
Fire/Explosion Hazard:	If safe to do so, move undamaged containers from fire area. Hazardous Decomposition Products: Decomposes on heating emitting oxides of carbon. Fire Fighting Procedures: Fire fighters to wear Self-contained breathing apparatus (SCBA) in confined spaces, in oxygen deficient atmospheres or if exposed to products of decomposition. Full protective clothing is also recommended. Extinguishing Media: Use extinguishing media suitable for surrounding fire situation.

OTHER INFORMATION

Incompatibilities (Materials to avoid)	Strong alkalis, acids, oxidizing agents.
Animal Toxicity Data:	

The information published in this Material Safety Data Sheet has been compiled from data in various technical publications. It is the user's responsibility to determine the suitability of this information for adoption of necessary safety precautions. We reserve the right to revise Material Safety Data Sheets as new information becomes available. Copies may be made for non-profit use.